


HUBNETIX Category 5e F/UTP 4 Pair 24 AWG Cable



Product Description

- Reference standard : UL444, UL1581
- Bare solid copper conductor
- RoHS/Reach complied PVC , PE , LSZH jacket
- Complies to ANSI/TIA-568-C.2, ISO/IEC 11801
- Installation temperature : -30°C ~ +50°C
- Minimum bending radius : 4D

Application

- Ethernet
- 10 Base - T
- 100 Base - T4
- ATM
- TP-PMD Speech
- Telephone
- Multimedia
- Trunk Wiring

Electrical Specifications

Frequency MHz	Impedance ohm	RL ≥dB	Attenuation ≤dB / 100m	NEXT ≥dB / 100m	ELFEXT ≥dB / 100m	PS NEXT ≥dB / 100m	PS ELFEXT ≥dB / 100m	NVP
1	100 ± 15	20.0	2.0	65.3	63.8	62.3	60.8	68%
4		23.0	4.1	56.3	51.7	53.3	48.7	
10		25.0	6.5	50.3	43.8	47.3	40.8	
16		25.0	8.2	47.3	39.7	44.2	36.7	
20		25.0	9.3	48.5	37.7	42.8	34.7	
31.25		23.6	11.6	42.9	33.9	39.9	30.9	
62.5		21.5	17.0	38.4	27.8	35.4	24.8	
100		20.0	22.0	35.3	23.8	32.3	20.8	
*155	100 ± 18	18.8	28.1	32.4	20.2	29.4	17.2	
*200		18.0	32.4	30.8	18.0	27.8	15.0	
*310	100 ± 22	16.7	41.8	27.9	14.2	24.9	11.2	
*350		16.3	44.9	27.1	13.1	24.1	10.1	

*Reference values

Cable Construction

Item Number	Construction	Conductor AWG	Nominal Insulation ØMM	No. of Pairs	Nominal Cable OD.	Type of Jacket	Remark
HLZ-5EF0424A-XX	F/UTP	24	0.93	4	6.3	PVC / PE / LSZH / PVC+PE	100MHz
HLZ-5EF0424B-XX	F/UTP	24	0.94	4	6.4	PVC / PE / LSZH	350MHz

*XX=01(for PVC);XX=02(for PE);XX=03(for LSZH), XX=05 (PVC+PE)

HUBNETIX CORPORATION
71-75, Shelton Street, London, UK.
www.hubnetix.com

The dimensions and specifications in this document are for reference purposes only and are subject to change without notice. Consult HUBNETIX Corp. for the latest dimensions and design specifications.

