



Description

LANLINE Uni-tube Indoor-Outdoor Fibre Optic Cable is a key part of HUBNETIX Fibre Optic Cabling System. The Single Loose tube design offer a low cost to traditional stranded loose tube cables. The cable design support reliable transmission performance over a broad temperature range. The construction is suitable for Indoor and Outdoor use in Trunk, Distribution, Metro, Long-haul and broadband network applications. The rugged single loose tube design features optical fibres placed inside a single gel-filled tube. The core tube includes up to 24 distinctly colored Fibres. The core tube is then helically wrapped with water-blocking strength members, then encased with an HDPE jacket. LANLINE Uni-tube Indoor-Outdoor Fibre cables are available in fibre counts from 2 to 24 fibres. These OM1, OM2, OM3, OM4 multimode, and OS2 singlemode Indoor-Outdoor FO cables are compliant with IEC 60794, EIA/TIA, ITU-T international standards.

Standard Compliance

- Telecordia GR-20, IEC 60794
- EIA/TIA, ITU-T, EN187000, RUS1755.900

Environmental Specifications (Temperature)

- Operation / Storage : -20°C to +60°C
- Installation : -15°C to +65°C

Features

- Available Fibre counts from 2F to 24F
- Multiple Fibre includes – Multimode-OM1, OM2, OM3, OM4; OS1, OS2 Singlemode and Hybrid
- Small Cable diameter
- Multi-Tube designs are available from 12-144 Fibres

Application

- Duct, Indoor and Outdoor
- Trunk, Distribution and feeder cable
- Local loop, metro, long-haul and broadband network

Advantages

- High fibre density
- Multiple network applications
- Reduces cable preparation and installation time
- Reduces cost
- Installation of more Fibres in less space

Physical Characteristics

Fibre Count	Cable Outer Diameter (mm) Nominal	Weight (kg/km) (Nominal)	Tensile Strength (Nominal)		Crush Resistance (N/10cm)	Bending Radius (mm)	
			Installation	Operation		Temporary	Permanent
2-12	9.0	62	2000	1000	2000	90	180
12-24	10.0	80	2000	1000	2000	100	200

Uni-Tube Indoor-Outdoor Fibre Optic Cable



Fibre Technical Specifications

Optical Characteristics

Multi-Mode - Fibre Type & Grade

Characteristics	Conditions	Specified Values		Units
		62.5/125µm – OM1	50/125µm – OM2/OM3/OM4	
Attenuation	850nm	≤ 3.5	≤ 3.0	dB/km
	1300 nm	≤ 1.5	≤ 1.0	dB/km
Bandwidth	850 nm	≥ 200	≥ 500 / ≥ 1500 / ≥ 3500	MHz.km
	1300 nm	≥ 600	≥ 500 / ≥ 500 / ≥ 500	MHz.km
Ethernet Performance 10GBE	850nm	33	150 /300/ 550	m
Ethernet Performance 1000GBE	850nm	220	750 /1000/ 1100	m
Numerical Aperture		0.275 ± 0.015	0.200 ± 0.015	

Geometrical Characteristics

Core Diameter		62.5 ± 2.5	50.0 ± 2.5	µm
Core Non – Circularity		≤ 5.0	≤ 5.0	%
Core/Cladding Concentricity Error		≤ 1.5	≤ 1.5	µm
Cladding Diameter		125.0 ± 1.0	125.0 ± 1.0	µm
Cladding Non – Circularity		≤ 1.0	≤ 1.0	%
Primary Coating Diameter		245 ± 10	245 ± 10	µm
Coating/Cladding Concentricity Error		≤ 12	≤ 12	µm
Primary Coating Material (Colored)		UV Cured Acrylate	UV Cured Acrylate	

Mechanical Characteristics

Bending Induced Attenuation				
10 Turns @60mm Radius	850nm	≤ 0.5		dB
	1300 nm	≤ 0.5		dB
100 Turns @ 37.5mm Radius	850nm		≤ 0.50	dB
	1300 nm		≤ 0.50	dB
2 Turns @ 15mm Radius	850nm		≤ 1.0	dB
	1300 nm		≤ 1.0	dB
Proof Stress Level		≤ 1.0	≤ 1.0	%
		≤ 100	≤ 100	kpsi

Optical Characteristics

Single-Mode - Fibre Type & Grade

Characteristics	Conditions	Specified Values			Units
		ITU-T G.652.D	ITU-T G.657.A1	ITU-T G.657.A2	
Attenuation	1310 nm	≤ 0.36	≤ 0.36	≤ 0.38	dB/km
	1550 nm	≤ 0.23	≤ 0.23	≤ 0.23	dB/km
Chromatic Dispersion	1285 - 1330 nm		≤ 3.5		ps/(nm.km)
	1550 nm		≤ 18.0		ps/(nm.km)
Cable cutoff wavelength λ _{cc}			≤ 1260		nm
Zero Dispersion wavelength			1300 - 1324		nm
Zero Dispersion slope			≤ 0.092		ps/nm ² .km
Polarization mode Dispersion (PMD)	Fibre		≤ 0.2		ps/km
	Link Design Value		≤ 0.08		ps/km

Geometrical Characteristics

Mode Field Diameter (MFD)	1310 nm	9.2 ± 0.4	8.6 ± 0.4	6.3 ± 9.5	µm
	1550 nm	10.4 ± 0.5	9.8 ± 0.5		µm
Cladding Diameter			125.0 ± 1.0		µm
Cladding Non – Circularity			≤ 1.0		%
Core/Cladding Concentricity Error			≤ 0.5		µm
Coating/Cladding Concentricity Error			≤ 12.0		µm
Primary Coating Diameter			245 ± 10		µm
Primary Coating Material (Colored)			UV Curved Acrylate		
Fibre Curl (Radius)			≥ 4		m

Note- The optical attenuation/PMD given values may change due to fibre cabling.

Mechanical Characteristics - SM

Single-Mode - Fibre Type & Grade

	Conditions	Specified Values			Units
		ITU-T G.652.D	ITU-T G.657.A1	ITU-T G.657.A2	
Bending Induced Attenuation					
1 Turn @32mm Diameter	1550 nm		≤ 0.05		dB
100 Turns @ 50mm Diameter	1310 nm		≤ 0.05		dB
	1550 nm		≤ 0.05		dB
100 Turns @ 60mm Diameter	1625 nm		≤ 0.05		dB
Proof Stress Level			≥ 1.00		%
			≥ 100		kpsi

Environmental Characteristics

Environmental Tests				
Temperature Dependence	-60 to +85°C		≤ 0.05	dB/km
Temperature-Humidity Cycling	-10 to +85°C		≤ 0.05	dB/km
Water Immersion	23		≤ 0.05	dB/km
Dry Heat Aging	85		≤ 0.05	dB/km
Damp Heat	85°C @ 85% RH		≤ 0.05	dB/km

Uni-Tube Indoor-Outdoor Fibre Optic Cable



Ordering Info & Part Numbers

Part Number Example	Description
HLH-FUUM3L12-XX	LANLINE 12-Fibre, OM3 MM, Uni-tube, Indoor/Outdoor, LSZH, Fibre Cable

HUBNETIX Prefix			1	2	3	4	5	6
H	L	H	F	UU	M3	L	12	XX

1=F - Fibre Optic	2=Cable construction	3=Fibre type	4=Flame Rating	5=XX - Fibre Count	6=XX - Fibre Color code
	UM – Indoor/Outdoor Multi-tube	S1 – Singlemode OS1 9/125µm	L – Low Smoke Zero Halogen	02 – 02-fibre	OR – ORANGE (OM1/OM2)
	UU – Indoor/Outdoor Uni-tube	S2 – Singlemode OS2 9/125µm (ITU G.652.D)	H – HDPE	04 – 04-fibre	AQ – AQUA (OM3/OM4)
		M1 – Multimode OM1 62.5/125µm	P – PVC	06 – 06-fibre	YL – YELLOW (OS1/OS2)
		M2 – Multimode OM2 50/125µm		08 – 08-fibre	BK – BLACK
		M3 – Multimode OM3 50/125µm		12 – 12-fibre	
		M4 – Multimode OM4 50/125µm			
				24 – 24-fibre	
				36 – 36-fibre	
				48 – 48-fibre	
				72 – 72-fibre	
				96 – 96-fibre	

Note: All packaging is 2,000 mtr drum reel. The above shown cable designs are HUBNETIX standard designs. Other lengths and customised designs are available upon specific request.

HUBNETIX CORPORATION
71-75, Shelton Street, London, UK.
www.hubnetix.com

The dimensions and specifications in this document are for reference purposes only and are subject to change without notice. Consult HUBNETIX Corp. for the latest dimensions and design specifications.

